

In the Claims:

Amend the claims as follows:

5

1. (Currently amended) A tuner as constituent component for constructing a tunable or switchable spectral filter over a wavelength range comprising elements arranged in cascade along a light beam axis characterized by  
10 a dispersive polarization rotator (31), having its rotation angle  $\rho(\lambda)$  varying as a function of light wavelength  $\lambda$  over said wavelength range;  
an orientation-sensitive polarizing element, and  
means for rotating said polarizing element or/and varying said  
15 rotation angle  $\rho(\lambda)$ ;  
whereby said polarization rotator and said polarizing element are arranged in series in said spectral filter along said light beam axis with said polarizing element oriented at a predetermined orientation angle related to the structure of  
20 said spectral filter,  
and said tuner is operated by rotating said polarizing element to change its orientation in said filter or/and by changing said rotation angle  $\rho(\lambda)$ . ~~{Ex. FIGS. 6a-e}~~

25

2. (Currently amended) The tuner of claim 1 is characterized in that said polarization rotator preferably is a dispersive optical rotator, typically a quartz optical rotator, or a dispersive Faraday rotator, to which a magnetic field is applied, ~~having that has~~ the rotation angle changeable by  
30 adjusting the a magnetic flux density of said magnetic field  
~~and said polarizing element preferably is a polarizer,~~  
~~typically a dichroic or birefringent polarizer, or an optical~~  
~~retarder selected preferably from achromatic or zero order~~  
~~birefringent retarders, equivalent liquid crystal electrically~~

~~rotatable retarders, including FLC cells, SmA\* cells, DHF liquid crystal cells, SSFLC cells, planar aligned smectic C\* cells and ternary state antiferroelectric effect LC cells, and variable retarders, including liquid crystal variable~~  
5 ~~retarders such as nematic or homeotropically aligned smectic LC cells and phase modulators such as electro-optical, photo-elastic and magnetic modulators.~~

3. (Currently amended) The tuner of claim 1 is characterized  
10 in that said polarizing element is a polarizer (32), used as the exit or entrance polarizer of said filter and having its azimuth P relative to the reference axis of said filter, said polarization rotator (31) and said polarizer (32) are arranged  
15 in said spectral filter along said light beam axis with said polarization rotator followed or preceded by said polarizer, and said tuner is a polarizer-tuner (33), which is equivalent to a polarizer having the azimuth equal to  $P + \rho(\lambda)$  or  $P - \rho(\lambda)$   
varying as a function of light wavelength  $\lambda$  over said  
wavelength range, and is operated by changing said azimuth P  
20 or/and said rotation angle  $\rho(\lambda)$  to change said azimuth  $P + \rho(\lambda)$  or  $P - \rho(\lambda)$  of said polarizer-tuner. ~~[Ex. FIG. 6a]~~

4. (Currently amended) The tuner of claim 1 is characterized  
in that said polarizing element is a retarder (34), having its  
25 retardation  $\Delta$  equal or approximately equal to a predetermined value related to the structure of said spectral filter over said wavelength range, said polarization rotator (31) and retarder (34) are arranged in said spectral filter along said light beam axis with said retarder having its optic axis  
30 oriented at a predetermined angle  $\phi$  related to the structure of said spectral filter in said filter, and said tuner is equivalent to a series connection of an equivalent optical rotator (36) of rotation angle  $\rho(\lambda)$  and a retarder-tuner (35),

which is equivalent to a retarder having its retardation equal to  $\Delta$  and the orientation angle of its optic axis equal to  $\phi + \rho(\lambda)$  or  $\phi - \rho(\lambda)$  over said wavelength range, and operated by changing said orientation angle  $\phi$  or/and said rotation angle  $\rho(\lambda)$  to change said orientation angle  $\phi + \rho(\lambda)$  or  $\phi - \rho(\lambda)$  of said retarder-tuner or/and by changing said retardation  $\Delta$ . ~~{Ex- FIG. 6b}~~

5. (Currently amended) The tuner of claim 4 is characterized in that said tuner further comprises a second dispersive polarization rotator (37) having its rotation angle  $-\rho(\lambda)$  varying as a function of light wavelength  $\lambda$  over said wavelength range, positioned on the opposite side of said retarder (34) from said rotator (31) of rotation angle  $\rho(\lambda)$ , said tuner is a retarder-tuner (35) equivalent to a retarder having its retardation equal to  $\Delta$  and the orientation angle of its optic axis equal to  $\phi + \rho(\lambda)$  or  $\phi - \rho(\lambda)$  over said wavelength range, operated by changing said orientation angle  $\phi$  or/and by simultaneously changing said rotation angles  $\rho(\lambda)$  and  $-\rho(\lambda)$  to change said orientation angle  $\phi + \rho(\lambda)$  or  $\phi - \rho(\lambda)$  of said retarder-tuner or/and by changing said retardation  $\Delta$ . ~~{Ex- FIG. 6c}~~

6. (Currently amended) A spectral filter over a wavelength range comprising elements arranged in cascade along a light beam axis ~~according to claims 3, 4 and 5~~ characterized by  
an entrance polarizer;  
at least a dispersive polarization rotator with the rotation angle varying as a function of light wavelength over said wavelength range;  
at least an orientation-sensitive polarizing element; and

means for rotating said orientation-sensitive polarizing element(s) about said light beam axis or/and varying said rotation angle(s); whereby

5 said polarizing element or at least one of said polarizing elements is a polarizer, said polarization rotator(s) and polarizing element(s) are arranged behind said entrance polarizer along said beam axis to form tuner(s) ~~according to~~  
~~claims 3, 4 and 5~~ such that said polarizing element that is a polarizer works as the exit polarizer of said filter, and said  
 10 filter has its spectral transmission determined by said rotation angle(s) and tunable by rotating said exit polarizer or/and the other(s) of said polarizing element(s) about said beam axis and further tunable by varying said rotation angle(s). ~~{Ex. FIGS. 7-11, 14, 16-18, 22, 24, 25, 29}~~

15 7. (Currently amended) The spectral filter of claim 6 is characterized in that said polarization rotator(s) ~~preferably~~ is or are dispersive optical rotator(s), typically quartz optical rotator(s), or Faraday rotator(s), to which magnetic  
 20 field is or are applied, having the rotation angle(s) changeable by adjusting the magnetic flux density or densities of said magnetic field(s) and said polarizing element(s) ~~preferably~~ is or are polarizer(s), typically dichroic or birefringent polarizer(s), or retarder(s) selected ~~preferably~~  
 25 from achromatic or zero-order birefringent retarders, equivalent liquid crystal electrically rotatable retarders, including FLC cells, SmA\* cells, DHF liquid crystal cells, SSFLC cells, planar aligned smectic C\* cells and ternary state antiferroelectric-effect LC cells, and variable retarders,  
 30 including liquid crystal variable retarders such as nematic or homeotropically aligned smectic LC cells and phase modulators such as electro-optical, photo-elastic and magnetic modulators.

35 8. (Currently amended) The spectral filter of claim 6 is

characterized in that said filter is a single-stage spectral filter over said wavelength range comprising elements arranged in cascade along said light beam axis including an entrance polarizer (40);

5 a dispersive polarization rotator (41) with the rotation angle varying as a function of light wavelength over said wavelength range, selected ~~preferably~~ from optical rotators and Faraday rotators;

an exit polarizer (42); and

10 means for rotating said exit polarizer about said light beam axis;

whereby said polarization rotator (41) is sandwiched between said entrance and exit polarizers (40, 42) with the combination of said polarization rotator (41) and polarizer

15 (42) equivalent to a polarizer-tuner according to claim 3 and said filter has its spectral transmission determined by said rotation angle and tunable by rotating said exit polarizer about said beam axis relative to said entrance polarizer and further tunable by varying said rotation angle. ~~{Ex. FIGS. 7-10}~~

20 ~~10}~~

9. (Currently amended) The single-stage filter of claim 8 is characterized in that said polarization rotator (41) ~~preferably~~ is a dispersive optical rotator, typically a quartz

25 optical rotator, and the spectral transmission of said filter is tunable by rotating said exit polarizer (42) about said beam axis relative to said entrance polarizer (40). ~~{Ex. FIG. 7}~~

7}

30 10. (Currently amended) The single-stage filter of claim 8 is characterized in that said polarization rotator ~~preferably~~ (41) is a dispersive Faraday rotator, to which a magnetic field is applied, having the rotation angle changeable by adjusting the magnetic flux density of said

35 magnetic field, and said filter further comprises means for

changing the rotation angle of said Faraday rotator by adjusting the magnetic flux density of said magnetic field.  
~~{Ex. FIG. 7}~~

5           11. (Currently amended) The single-stage filter of claim  
10 is characterized in that said filter has its spectral transmission determined by said Faraday rotation angle and tunable by varying said Faraday rotation angle or switchable by switching said Faraday rotation angle in at least two  
10 alternative states, further tunable by rotating said exit polarizer (42) about said beam axis relative to said entrance polarizer (40), and functions as a one-direction device that transmits and tunably filters light in one direction, but blocks the backward light, with said exit polarizer preferably  
15 fixed and oriented at 45° relative to said entrance polarizer.  
~~{Ex. FIG. 7}~~

          12. (Currently amended) The single-stage filter of claim  
8 is characterized in that said polarization rotator  
20 preferably is a dispersive optical rotator (43), typically a quartz optical rotator, and said filter further comprises a rotatable half-wave retarder (44) having its retardation equal or approximately equal to 180° over said wavelength range, preferably an equivalent achromatic or zero-order birefringent  
25 retarder or liquid crystal electrically rotatable retarder, positioned immediately behind or before said optical rotator (43). ~~{Ex. FIG. 8}~~

          13. (Currently amended) The single-stage filter of claim  
30 12 is characterized in that the combination of said optical rotator (43) and retarder (44) is equivalent to a tuner according to claim 4 and said filter has its spectral transmission determined by said rotation angle of said optical rotator with and tunable by rotating said half-wave retarder  
35 about said light beam axis, mechanically or/and electrically,

and further tunable by rotating said exit polarizer (42) relative to said entrance polarizer (40). ~~{Ex. FIG. 8}~~

14. (Currently amended) The single-stage filter of claim 5 8 is characterized in that said polarization rotator preferably is a dispersive optical rotator (43), ~~typically a quartz-optical rotator,~~ said filter further comprises an active polarization rotator (45) having its rotation angle adjustable over said wavelength range, positioned immediately 10 before or behind said passive optical rotator (43), and means for changing the rotation angle of said active polarization rotator. ~~{Ex. FIG. 9}~~

15. (Currently amended) The single-stage filter of claim 15 14 is characterized in that the combination of said optical rotator (43), active polarization rotator (45) and polarizer (42) is equivalent to a polarizer-tuner according to claim 2 and said filter has its spectral transmission tunable or switchable by changing said rotation angle of said active 20 polarization rotator and further tunable by rotating said exit polarizer (42) relative to said entrance polarizer (42). ~~{Ex. FIG. 9}~~

16. (Currently amended) The single-stage filter of claim 25 15 is characterized in that said active polarization rotator (45) preferably is a Faraday rotator, to which a magnetic field is applied, having the rotation angle changeable by adjusting the magnetic flux density of said magnetic field, or a liquid crystal polarization rotator, having the rotation 30 angle continuously or discretely rotatable by application of a control voltage, typically a twisted-nematic liquid crystal polarization rotator, positioned immediately before said passive polarization rotator (43) and oriented with its entrance crystal axis parallel to the transmission axis of 35 said entrance polarizer (40). ~~{Ex. FIG. 9}~~

17. (Currently amended) The single-stage filter of claim 8 is characterized in that said exit polarizer (42) preferably is stationary and oriented parallel or perpendicular to said entrance polarizer (40) and said polarization rotator is a dispersive optical rotator (43), typically a quartz optical rotator, and said filter further comprises a second dispersive optical rotator (47), selected such that said second optical rotator and said initial optical rotator build up a pair of optical rotators having equal and opposite rotation angles over said wavelength range, a variable retarder (46) operated to work as a switchable retarder, having its retardation switchable between two alternative states such that said retarder has the retardation equal or approximately equal to zero in one of said states and 180° in the other, respectively, over said wavelength range, and means for operating said retarder with said retardation switchable in said states and rotating said retarder about said beam axis. ~~{Ex. FIG. 10}~~

18. (Currently amended) The single-stage filter of claim 17 is characterized in that said second optical rotator (47) and variable retarder (46) are arranged in series between said entrance and exit polarizers (40, 42) and positioned with said variable retarder (46) facing said initial optical rotator (43) and said filter has its spectral transmission determined by said rotation angles, with the combination of said optical rotator (43), variable retarder (46) and second optical rotator (47) equivalent to a retarder-tuner according to claim 5, and switchable by switching said retarder between said switched states and further tunable by rotating said retarder about said beam axis relative to said entrance polarizer. ~~{Ex. FIG. 10}~~

35



19. (Currently amended) The spectral filter of claim 6 is characterized in that said filter is an n-stage ( $n=2, 3, 4, \dots$ ) spectral filter over said wavelength range comprising elements arranged in cascade along said light beam axis including

5 an entrance polarizer ( $49_1$ );

$n-1$  intermediate polarizers ( $49_2, 49_3, \dots, 49_n$ );

$n$  dispersive polarization rotators ( $50_1, 50_2, \dots, 50_n$ ), which have their wavelength-dependent rotation angles in the ratios of integers, preferably in the ratios of  $1:2:4:8:\dots:2^{n-1}$

10 disregarding the rotation sense over said wavelength range and are selected preferably from optical rotators and Faraday rotators;

an exit polarizer ( $49_{n+1}$ ); and

15 means for rotating said exit polarizer and  $n-1$  intermediate polarizers about said light beam axis;

whereby said  $n-1$  intermediate polarizers ( $49_2, 49_3, \dots, 49_n$ ) and  $n$  polarization rotators ( $50_1, 50_2, \dots, 50_n$ ) are arranged between said entrance and exit polarizers ( $49_1, 49_{n+1}$ ); along

20 said light beam axis to form  $n$  stages in series, each containing a polarization rotator between polarizers according to claim 6, such that each of said intermediate polarizers ( $49_2, 49_3, \dots, 49_n$ ) serves as the exit polarizer of one stage and the entrance polarizer of the following adjacent stage and

25 such that the formed  $n$  stage exit polarizers ( $49_2, 49_3, \dots, 49_n, 49_{n+1}$ ) are oriented, each relative to its immediately preceding polarizer, with their azimuths in the same ratios as those of the rotation angles of the  $n$  polarization rotators ( $50_1, 50_2, \dots, 50_n$ ), which are immediately preceding said  $n$

30 stage exit polarizers, and said filter has its spectral transmission determined by said rotation angles and tunable by simultaneously rotating said  $n$  stage exit polarizers about said light beam axis with said ratios of their azimuths

remaining unchanged or such that said n stage exit polarizers are parallel or perpendicular to said entrance polarizer and further tunable by simultaneously varying said rotation angles of said n polarization rotators with said ratios of said rotation angles remaining unchanged. ~~{Ex. FIGS. 11, 14, 16, 17}~~

20. (Currently amended) The spectral filter of claim 19 is characterized in that said n polarization rotators (50<sub>1</sub>, 50<sub>2</sub>, ..., 50<sub>n</sub>) preferably are dispersive optical rotators with their wavelength-dependent rotation angles in said ratios of integers over said wavelength range and the spectral transmission of said filter is tunable by simultaneously rotating said n stage exit polarizers (49<sub>2</sub>, 49<sub>3</sub>, ..., 49<sub>n+1</sub>) about said beam axis with said ratios of their azimuths remaining unchanged or such that said n stage exit polarizers are parallel or perpendicular to said entrance polarizer. ~~{Ex. FIG. 11}~~

21. (Currently amended) The spectral filter of claim 19 is characterized in that said n polarization rotators (50<sub>1</sub>, 50<sub>2</sub>, ..., 50<sub>n</sub>) preferably are dispersive Faraday rotators with their wavelength-dependent rotation angles in said ratios of integers over said wavelength range, to which magnetic fields are applied, respectively, and said filter further comprises means for changing said Faraday rotation angles by adjusting the magnetic flux densities of said magnetic fields. ~~{Ex. FIG. 11}~~

22. (Currently amended) The spectral filter of claim 21 is characterized in that said filter has its spectral transmission determined by said Faraday rotation angles and tunable by simultaneously varying said Faraday rotation angles or switchable by simultaneously switching said Faraday

rotation angles in at least two alternative states such that said Faraday rotation angles have their said ratios remaining unchanged or said Faraday rotation angles are equal or approximately equal to zero over said wavelength range,  
5 further tunable by simultaneously rotating said n stage exit polarizers about said light beam axis with said ratios of their azimuths remaining unchanged or such that said n stage exit polarizers are parallel or perpendicular to said entrance filter, and functions as a one-direction device that transmits  
10 and tunably filters light in one direction, but blocks the backward light, with said n stage exit polarizers preferably stationary and oriented such that the stage exit polarizer, which immediately follows the Faraday rotator of the smallest rotation angle among said n Faraday rotation angles, is  
15 oriented preferably at  $45^\circ$  related to its immediately preceding polarizer and the rest n-1 stage exit polarizers are parallel or perpendicular to said entrance polarizer. ~~{Ex- FIG. 11}~~

20       23. (Currently amended) The spectral filter of claim 19 is characterized in that said n polarization rotators preferably are dispersive optical rotators ( $51_1, 51_2, \dots, 51_n$ ), typically quartz optical rotators, with their wavelength-dependent rotation angles in said ratios of  
25 integers over said wavelength range, said n stage exit polarizers ( $49_2, 49_3, \dots, 49_{n+1}$ ) are oriented preferably parallel or perpendicular to said entrance polarizer, and said spectral filter further comprises n rotatable half-wave retarders ( $52_1, 52_2, \dots, 52_n$ ), each having its retardation  
30 equal or approximately equal to  $180^\circ$  over said wavelength range, positioned respectively immediately behind or before said arranged n optical rotators ( $51_1, 51_2, \dots, 51_n$ ) such that each of said stages is ~~in accordance with claim 12 and~~ oriented such that said n half-wave retarders are parallel to

their immediately preceding polarizers, respectively, or have their orientation angles, each relative to its immediately preceding polarizer, in the same ratios as those of said rotation angles of said arranged  $n$  optical rotators. ~~{Ex. FIG. 14}~~

5

24. (Currently amended) The spectral filter of claim 23 is characterized in that said  $n$  retarders ( $52_1, 52_2, \dots, 52_n$ ) ~~preferably~~ are achromatic or zero-order birefringent retarders or equivalent liquid crystal electrically rotatable retarders oriented, each relative to its immediately preceding polarizer, such that their orientation angles in the same ratios as those of the rotation angles of said arranged  $n$  optical rotators ( $51_1, 51_2, \dots, 51_n$ ) and the spectral transmission of said filter is determined by said rotation angles of said optical rotators and tunable by simultaneously rotating said  $n$  birefringent retarders or liquid crystal retarders about said light beam axis, mechanically or/and electrically, with said ratios of their said orientation angles remaining unchanged or such that said orientation angles are equal to zero and can further be tunable by simultaneously rotating said  $n$  stage exit polarizers with their azimuths, each relative to its immediately preceding polarizer, in said ratios of their immediately preceding optical rotation angles. ~~{Ex. FIG. 14}~~

10

15

20

25

25. (Currently amended) The spectral filter of claim 19 is characterized in that said  $n$  polarization rotators ~~preferably~~ are dispersive optical rotators ( $51_1, 51_2, \dots, 51_n$ ), typically quartz optical rotators, having their wavelength-dependent rotation angles in said ratios of integers over said wavelength range, said  $n$  stage exit polarizers ( $49_2, 49_3, \dots, 49_{n+1}$ ) ~~preferably~~ are stationary and oriented parallel or perpendicular to said entrance polarizer,

30

and said filter further comprises n active polarization rotators ( $53_1, 53_2, \dots, 53_n$ ), which have their rotation angles adjustable over said wavelength and are positioned immediately before or behind said n passive optical rotators ( $51_1, 51_2, \dots, 51_n$ ), respectively, ~~such that each of said stages is in accordance with claim 14 and the rotation angles of said arranged n active polarization rotators ( $53_1, 53_2, \dots, 53_n$ ) are in the same ratios as those of their immediately following or preceding n optical rotators over said wavelength range, and means for changing the rotation angles of said n active polarization rotators, and said filter has its spectral transmission tunable or switchable by simultaneously changing said active rotation angles with said ratios of said active rotation angles remaining unchanged or equal or approximately equal to zero over said wavelength range and further tunable by simultaneously rotating said n stage exit polarizers ( $49_2, 49_3, \dots, 49_{n+1}$ ) with their azimuths, each relative to its immediately preceding polarizer, in said ratios of their immediately preceding optical rotation angles. {Ex. FIG. 16}~~

26. (Currently amended) The spectral filter of claim 25 is characterized in that said n active polarization rotators ( $53_1, 53_2, \dots, 53_n$ ), preferably are Faraday rotators, to which magnetic fields are respectively applied, having the rotation angles changeable by adjusting the magnetic flux densities of said magnetic fields, or equivalent liquid crystal polarization rotators, having their rotation angles continuously or discretely adjustable, positioned immediately before or behind said n optical rotators ( $51_1, 51_2, \dots, 51_n$ ), respectively, such that said arranged n Faraday rotators or liquid crystal rotators have their rotation angles in the same ratios as those of their immediately following or preceding n optical rotators or equal or approximately equal to zero when being switched on or off over said wavelength range, and the

spectral transmission of said filter is tunable or switchable by simultaneously adjusting said rotation angles of said Faraday rotators or liquid crystal rotators with said ratios of said rotation angles remaining unchanged or equal or approximately equal to zero over said wavelength range. ~~{Ex- FIG. 16}~~

27. (Currently amended) The spectral filter of claim 26 is characterized in that said n liquid crystal polarization rotators (53<sub>1</sub>, 53<sub>2</sub>, ..., 53<sub>n</sub>) ~~preferably~~ are twisted-nematic liquid crystal polarization rotators, positioned respectively immediately before said n optical rotators (51<sub>1</sub>, 51<sub>2</sub>, ..., 51<sub>n</sub>) and oriented with the entrance crystal axis of each of said twisted-nematic rotators parallel to the transmission axis of its immediately preceding polarizer, said twisted-nematic rotators have their rotation angles equal or approximately equal to zero or in the same ratios as those of their immediately following n optical rotators over said wavelength range when said twisted-nematic rotators are switched on and off, respectively, and the spectral transmission of said filter is switchable by simultaneously switching said twisted-nematic liquid crystal polarization rotators on and off. ~~{Ex- FIG. 16}~~

28. (Currently amended) The spectral filter of claim 19 is characterized in that said formed n stage exit polarizers (49<sub>2</sub>, 49<sub>3</sub>, ..., 49<sub>n+1</sub>) ~~preferably~~ are stationary and oriented parallel or perpendicular to said entrance polarizer (49<sub>1</sub>), said n polarization rotators ~~preferably~~ are dispersive optical rotators (51<sub>1</sub>, 51<sub>2</sub>, ..., 51<sub>n</sub>), typically quartz optical rotators, having their wavelength-dependent rotation angles in said ratios of integers over said wavelength range, and said filter further comprises another n dispersive optical rotators (54<sub>1</sub>, 54<sub>2</sub>, ..., 54<sub>n</sub>),

selected such that said another  $n$  optical rotators ( $54_1, 54_2, \dots, 54_n$ ), and said initial  $n$  optical rotators ( $51_1, 51_2, \dots, 51_n$ ) build up  $n$  pairs of optical rotators, each having equal and opposite rotation angles over said wavelength range, and  
5 positioned such that each of said  $n$  stages contains a pair of optical rotators having equal and opposite rotation angles,  $n$  identical variable retarders ( $55_1, 55_2, \dots, 55_n$ ), operated to work as switchable retarders, each having its retardation switchable between two alternative states such that its  
10 retardation is equal or approximately equal to zero in one of said states and  $180^\circ$  in the other, respectively, over said wavelength range, and positioned such that each of said  $n$  stages contains one of said retarders, sandwiched between the optical rotators of this stage, ~~in accordance with claim 17~~  
15 and means for switching said  $n$  retarders and rotating said  $n$  retarders about said beam axis. ~~{Ex. FIG. 17}~~

29. (Currently amended) The spectral filter of claim 28 is characterized in that said positioned  $n$  variable retarders  
20 ( $55_1, 55_2, \dots, 55_n$ ) are oriented parallel to said entrance polarizer or with their orientation angles, each relative to its immediately preceding polarizer, in the same ratios as those of the rotation angles of their immediately preceding optical rotators, and said filter has its spectral  
25 transmission determined by said rotation angles and switchable by simultaneously switching said  $n$  retarders ( $55_1, 55_2, \dots, 55_n$ ) in said switched states and further tunable by simultaneously rotating said  $n$  retarders about said beam axis with said ratios of said orientation angles remaining  
30 unchanged or such that each of said  $n$  retarders is parallel or perpendicular to its immediately preceding polarizer. ~~{Ex. FIG. 17}~~

30. (Currently amended) The spectral filter of claim 6 is

characterized in that said filter is a two-tuner spectral filter without intermediate polarizer ~~according to claim 5~~ over said wavelength range comprising elements arranged in cascade along said light beam axis including

5 an entrance polarizer (61);  
a first polarization rotator (62), having its rotation angle  $\rho_{s1}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
a first retarder (63);  
a second polarization rotator (64), having its rotation angle  
10  $\rho_{s2}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
a second retarder (65);  
a third polarization rotator (66), having its rotation angle  $\rho_{s3}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
an exit polarizer (67); and  
15 means for rotating said first and second retarders about said beam axis;

whereby said rotation angles  $\rho_{s1}(\lambda)$ ,  $\rho_{s2}(\lambda)$  and  $\rho_{s3}(\lambda)$  are in the ratios of  $\rho_{s1}(\lambda):\rho_{s2}(\lambda):\rho_{s3}(\lambda)=1:-2:1$  over said wavelength range, said first and second retarders (63, 65) are identical,  
20 having the retardation  $\Delta$  equal or approximately equal to a predetermined value, selected ~~preferably~~ between  $80^\circ$  and  $115^\circ$ , over said wavelength range, said entrance and exit polarizers are oriented parallel to each other, having their transmission axes at  $45^\circ$  relative to a selected reference axis, and said  
25 first polarization rotator (62), first retarder (63), second polarization rotator (64), second retarder (65) and third polarization rotator (66) are arranged in the recited order between said entrance and exit polarizers (61, 67), with said retarders (63, 65) oriented, having their optic axes symmetric  
30 about said reference axis, respectively at angles  $\phi$  and  $-\phi$  apart from, as viewed along said beam axis. ~~{Ex. FIG. 18}~~

31. (Currently amended) The spectral filter of claim 30



is characterized in that the combination of said rotators (62, 64, 66) and retarders (63, 65) is equivalent to a series connection of two retarder-tuners (68, 69) ~~in accordance with claim 5~~ having identical retardation  $\Delta$  and their orientation angles respectively equal to  $-(\rho_{s1}(\lambda)+\varphi)$  and  $(\rho_{s1}(\lambda)+\varphi)$  relative to said reference axis and said filter has

its spectral transmission determined by said rotation angles, defined by Equation (24), and tunable by simultaneously rotating said retarders (63, 65) in opposite directions about said beam axis with their optic axes keeping symmetric about said reference axis and further tunable by simultaneously varying said rotation angles  $\rho_{s1}(\lambda)$ ,  $\rho_{s2}(\lambda)$  and  $\rho_{s3}(\lambda)$  with their said ratios of 1:-2:1 remaining unchanged over said wavelength range,

its spectral transmission equivalent to that of a Šolc type two-plate filter when said retarders (63, 65) have their retardation equal or approximately equal to  $90^\circ$  over said wavelength range,

the bandwidth of its transmission peaks adjustable by simultaneously varying said retardation of said retarders ~~preferably~~ in the range from  $80^\circ$  to  $115^\circ$  over said wavelength range, and

its spectral transmission inverted to work as a notch filter that tunably transmits and blocks light at wavelengths where said initial filter blocks and transmits light, respectively, when said exit polarizer (67) is rotated by  $90^\circ$  from said initial orientation to be perpendicular to said entrance polarizer (61). ~~{Ex. FIG. 18}~~

32. (Currently amended) The spectral filter of claim 30 is characterized in that said first, second and third polarization rotators (62, 64, 66) ~~preferably~~ are dispersive optical rotators with their rotation angles in said ratios of

1:-2:1 over said wavelength range and said retarders (63, 65) preferably are equivalent birefringent retarders or liquid crystal electrically rotatable retarders with their optic axes oriented symmetric about said reference axis, and said filter  
5 has its spectral transmission tunable by simultaneously rotating said birefringent retarders or liquid crystal retarders, mechanically or/and electrically, in opposite directions about said beam axis with their optic axes keeping symmetric about said reference axis or such that said  
10 birefringent retarders or liquid crystal retarders are parallel to said entrance polarizer (61). ~~[Ex. FIG. 18]~~

33. (Currently amended) The spectral filter of claim 30 is characterized in that said first, second and third  
15 polarization rotators (62, 64, 66) preferably are dispersive Faraday rotators, to which magnetic fields are respectively applied, having their rotation angles in said ratios of 1:-2:1 over said wavelength range and said retarders (63, 65) preferably are equivalent birefringent retarders with their  
20 optic axes oriented symmetric about said reference axis, respectively at angles  $\phi$  and  $-\phi$  apart from, as viewed along said beam axis, and said filter further comprises means for varying said Faraday rotation angles by adjusting the magnetic flux densities of said magnetic fields.

25  
34. (Currently amended) The spectral filter of claim 33, is characterized in that said filter has its spectral transmission tunable or switchable by simultaneously varying said Faraday rotation angles or switching said Faraday  
30 rotation angles in at least two alternative states with said ratios of 1:-2:1 of said Faraday rotation angles remaining unchanged over said wavelength range and functions as a one-direction device that transmits and tunably filters light in one direction, but blocks the backward light, with said

birefringent retarders having their retardation preferably equal or approximately equal to  $99.8^\circ$  over said wavelength range and oriented with their optic axes preferably at  $\phi=22.5^\circ$  and  $-\phi=-22.5^\circ$  relative to said reference axis, respectively.

5 ~~{Ex. FIG. 18}~~

35. (Currently amended) The spectral filter of claim 30 is characterized in that said first, second and third polarization rotators (62, 64, 66) preferably are equivalent  
10 dispersive optical rotators and said retarders (63, 65) preferably are variable retarders oriented with their optic axes symmetric about said reference axis, each having its retardation variable preferably in the range from  $80^\circ$  to  $115^\circ$  or/and switchable in at least two alternative states such that  
15 said variable retarders have their retardation equal or approximately equal to  $0^\circ$  in one of said switched states and equal or approximately equal to value(s), selected preferably between  $80^\circ$  and  $115^\circ$ , in the other state(s) over said wavelength range. ~~{Ex. FIG. 18}~~

20

36. (Currently amended) The spectral filter of claim 35 is characterized in that said filter has the bandwidth of its spectral transmission peaks adjustable by simultaneously varying said retardation of said variable retarders (63, 65),  
25 and its spectral transmission tunable by simultaneously rotating said variable retarders in opposite directions with their optic axes keeping symmetric about said reference axis and switchable by simultaneously switching said variable retarders (63, 65) with their said retardation switched in  
30 said states. ~~{Ex. FIG. 18}~~

37. (Currently amended) The spectral filter of claim 6 is characterized in that said filter is a three-tuner spectral filter without intermediate polarizer ~~according to claims 3~~

and ~~5~~ over said wavelength range comprising elements arranged in cascade along said light beam axis including an entrance polarizer (71);  
a first polarization rotator (72), having its rotation angle  $\rho_{11}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
a first quarter-wave retarder (73);  
a second polarization rotator (74), having its rotation angle  $\rho_{12}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
a second quarter-wave retarder (75);  
10 a third polarization rotator (76), having its rotation angle  $\rho_{13}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
an exit polarizer (77); and  
means for rotating said retarders and said exit polarizer about said light beam axis;  
15 said rotation angles  $\rho_{11}(\lambda)$ ,  $\rho_{12}(\lambda)$  and  $\rho_{13}(\lambda)$  are in the ratios of  $\rho_{11}(\lambda):\rho_{12}(\lambda):\rho_{13}(\lambda)=1:1:-1$  over said wavelength range, said first and second quarter-wave retarders (73, 75) preferably are achromatic or zero-order retarders, having the retardation equal or approximately equal to  $90^\circ$  over said wavelength  
20 range, and said first polarization rotator (72), first quarter-wave retarder (73), second polarization rotator (74), second quarter-wave retarder (75) and third polarization rotator (76) are arranged in the recited order between said entrance and exit polarizers (71, 77), with said first and  
25 second quarter-wave retarders (73, 75) and said exit polarizer (77) oriented such that the orientation angles  $\phi_1$  and  $\phi_2$  of said first and second retarders (73, 75) and the azimuth  $P_2$  of said exit polarizer (77), relative to said entrance polarizer (71), are in the ratios of  $\phi_1:\phi_2:P_2=1:2:1$ . ~~{Ex. FIGS. 22, 24}~~

30

38. (Currently amended) The spectral filter of claim 37 is characterized in that the combination of said rotators (72,

74, 76), retarders (73, 75) and exit polarizer (77) is equivalent to a series connection of two retarder-tuners (78, 79) ~~in accordance with claim 5~~ and a polarizer-tuner (80) ~~according to claim 3~~ with said retarder-tuners having  
5 identical retardation equal or approximately equal to  $90^\circ$  and their orientation angles respectively equal to  $-(\rho_{11}(\lambda)+\phi_1)$  and  $(2\rho_{11}(\lambda)+\phi_2)$ , and said polarizer-tuner having its azimuth equal to  $\rho_{11}(\lambda)+P_2$ , and said filter has

its spectral transmission determined by said rotation  
10 angles, equivalent to that of a Lyot two-stage filter, and tunable by simultaneously rotating said first and second quarter-wave retarders (73, 75) and exit polarizer (77) about said light beam axis with said ratios of 1:2:1 of their orientation angles and azimuth remaining unchanged or such  
15 that said first and second quarter-wave retarders (73, 75) and exit polarizer (77) are parallel to said entrance polarizer, and

its spectral transmission inverted to work as a notch filter that tunably transmits and blocks light at wavelengths where  
20 said initial filter blocks and transmits light, respectively, when said exit polarizer (77) is oriented such that the orientation angles of said first and second retarders (73, 75) relative to said entrance polarizer (71) and the azimuth of said exit polarizer (77) relative to an axis perpendicular to  
25 said entrance polarizer (71) are in said ratios of 1:2:1. ~~[Ex-  
FIG. 22]~~

39. (Currently amended) The spectral filter of claim 37 is characterized in that said first, second and third  
30 polarization rotators (72, 74, 76) ~~preferably~~ are dispersive optical rotators with their rotation angles in said ratios of 1:1:-1 over said wavelength range, and said first and second quarter-wave retarders (73, 75) ~~preferably~~ are equivalent birefringent retarders, oriented with their orientation angles

and the azimuth of said exit polarizer (77), relative to said entrance polarizer (71), in said ratios of 1:2:1, and said filter has its spectral transmission tunable by simultaneously rotating said birefringent retarders (73, 75) and exit  
5 polarizer (77) about said light beam axis with their said ratios of 1:2:1 of their said orientation angles and azimuth remaining unchanged. ~~{Ex. FIG. 22}~~

40. (Currently amended) The spectral filter of claim 37  
10 is characterized in that said first, second, and third polarization rotators (72, 74, 76) preferably are dispersive Faraday rotators with their rotation angles in said ratios of 1:1:-1 over said wavelength range, to which magnetic fields are applied, respectively, and said first and second quarter-  
15 wave retarders (73, 75) preferably are equivalent birefringent retarders, oriented with their orientation angles and the azimuth of said exit polarizer (77), relative to said entrance polarizer (71), in said ratios of 1:2:1 and said filter further comprises means for electrically changing said Faraday  
20 rotation angles by adjusting the magnetic flux densities of said magnetic fields. ~~{Ex. FIG. 22}~~

41. (Currently amended) The spectral filter of claim 37  
25 is characterized in that said filter has its spectral transmission tunable by simultaneously changing said Faraday rotation angles with their said ratios of 1:1:-1 remaining unchanged and further tunable by simultaneously rotating said first and second birefringent retarders (73, 75) and exit polarizer (77) about said light beam axis with said ratios of  
30 1:2:1 of their said orientation angles and azimuth remaining unchanged or such that said birefringent retarders (73, 75) and exit polarizer (77) are parallel to said entrance polarizer (71) and functions as a one-direction device that transmits and tunably filters light in one direction, but

blocks the backward light, with said birefringent retarders (73, 75) and said exit polarizer (77) stationary and oriented relative to said entrance polarizer (71) ~~preferably~~ at 45°, 90° and 45°, respectively. ~~{Ex. FIG. 22}~~

5

42. (Currently amended) The spectral filter of claim 37 is characterized in that said first, second and third polarization rotators (72, 74, 76) are dispersive optical rotators with their rotation angles in said ratios of 1:1:-1 over said wavelength range and said exit polarizer (77) ~~preferably~~ is stationary and oriented parallel or perpendicular to said entrance polarizer, and said filter further comprises a rotatable half-wave retarder (81), having its retardation equal or approximately equal to 180° over said wavelength range, positioned between said third polarization rotator (76) and said exit polarizer (77) and oriented at angle  $\phi_3$  relative to said entrance polarizer (71) such that said first and second quarter-wave retarders (73, 75) and said half-wave retarder (81) are parallel to said entrance polarizer or have their orientation angles  $\phi_1$ ,  $\phi_2$  and  $\phi_3$  in the ratios of  $\phi_1:\phi_2:\phi_3 = 2:4:1$ . ~~{Ex. FIG. 24}~~

43. (Currently amended) The spectral filter of claim 42 is characterized in that said filter has its spectral transmission equivalent to that of a Lyot two-stage filter and tunable by simultaneously rotating said quarter-wave retarders (73, 75) and said half-wave retarder (81) about said light beam axis with said ratios of 2:4:1 of their said orientation angles remaining unchanged or such that said quarter-wave retarders (73, 75) and said half-wave retarder (81) are parallel to said entrance polarizer (71), and said quarter-wave retarders (73, 75) and said half-wave retarder (81) ~~preferably~~ are equivalent achromatic and zero-order birefringent retarders or liquid crystal electrically

rotatable retarders. ~~{Ex. FIG. 24}~~

44. (Currently amended) The spectral filter of claim 6 is characterized in that said filter is a three-tuner spectral filter without intermediate polarizer according to claim 5 over said wavelength range comprising elements arranged in cascade along said light beam axis including an entrance polarizer (82); a first polarization rotator (83), having its rotation angle  $\rho_{p1}(\lambda)$  varying as a function of light wavelength  $\lambda$ ; a first retarder (84); a second polarization rotator (85), having its rotation angle  $\rho_{p2}(\lambda)$  varying as a function of light wavelength  $\lambda$ ; a second retarder (86); a third polarization rotator (87), having its rotation angle  $\rho_{p3}(\lambda)$  varying as a function of light wavelength  $\lambda$ ; a third retarder (88); a fourth polarization rotator (89), having its rotation angle  $\rho_{p4}(\lambda)$  varying as a function of light wavelength  $\lambda$ ; an exit polarizer (90); and means for rotating said first, second and third retarders about said beam axis; said rotation angles  $\rho_{p1}(\lambda)$ ,  $\rho_{p2}(\lambda)$ ,  $\rho_{p3}(\lambda)$  and  $\rho_{p4}(\lambda)$  are in the ratios of  $\rho_{p1}(\lambda):\rho_{p2}(\lambda):\rho_{p3}(\lambda):\rho_{p4}(\lambda) = 1:-2:2:-1$  over said wavelength range, said first and third retarders (84, 88) are identical, having the retardation  $\Delta$  equal or approximately equal to a predetermined value selected preferably between  $60^\circ$  and  $100^\circ$  over said wavelength range, said second retarder (86) is a half-wave retarder, having its retardation equal or approximately equal to  $180^\circ$  over said wavelength range, and said first polarization rotator (83), first retarder (84), second polarization rotator (85), second retarder (86), third polarization rotator (87), third retarder (88) and fourth



polarization rotator (89) are arranged in the recited order between said entrance and exit polarizers (82, 90) and oriented such that said entrance polarizer (82) is parallel or at  $45^\circ$  relative to a selected reference axis, said exit  
5 polarizer (90) is perpendicular to said entrance polarizer (82), and said first and third retarders (84, 88) are parallel to each other and their optic axes and the optic axis of said second retarder (86) are at the opposite side of said reference axis, respectively at angles  $-\varphi$  and  $\varphi+45^\circ$  apart  
10 from, as viewed along said beam axis. ~~{Ex. FIG. 25}~~

45. (Currently amended) The spectral filter of claim 44 is characterized in that the combination of said rotators (83, 85, 87, 89) and retarders (84, 86, 88) is equivalent to a  
15 series connection of three retarder-tuners (91, 92, 93) ~~in accordance with claim 5~~ with the first and third ones (91, 93) having identical retardation equal to  $\Delta$  and parallel oriented at angle of  $-(\rho_{p1}(\lambda)+\varphi)$ , and the central one (92) having the retardation equal or approximately equal to  $180^\circ$  and  
20 orientation angle  $\rho_{p1}(\lambda)+\varphi+45^\circ$  and said filter has its spectral transmission determined by said rotation angles and defined by Equation (31A) or (31b) and tunable by simultaneously rotating said first, second and third retarders (84, 86, 88) about said beam axis in the same speed with said  
25 first and third retarders (84, 88) synchronously in one direction and said second retarder (86) in the opposite direction to change said angle  $\varphi$ , and further tunable by simultaneously varying said rotation angles  $\rho_{p1}(\lambda)$ ,  $\rho_{p2}(\lambda)$ ,  $\rho_{p3}(\lambda)$  and  $\rho_{p4}(\lambda)$  with their said ratios of 1:-2:2:-1 remaining  
30 unchanged over said wavelength range, its spectral transmission equivalent to that of a Šolc type three-plate filter or a Lyot two-stage filter when said predetermined value for the retardation of said first and

third retarders (84, 88) is  $75.52^\circ$  or  $90^\circ$ ,  
the bandwidth of its spectral transmission peaks adjustable by  
simultaneously varying said retardation of said first and  
third retarders (84, 88) preferably in the range from  $60^\circ$  to  
5  $100^\circ$  over said wavelength range, and

its spectral transmission inverted to work as a notch  
filter that tunably transmits and blocks light at wavelengths  
where said initial filter blocks and transmits light,  
respectively, when said exit polarizer (90) is rotated by  $90^\circ$   
10 from said initial orientation to be parallel to said entrance  
polarizer (82). ~~{Ex. FIG. 25}~~

46. (Currently amended) The spectral filter of claim 44  
is characterized in that said first, second, third and fourth  
15 polarization rotators (83, 85, 87, 89) preferably are  
dispersive optical rotators with their rotation angles in said  
ratios of 1:-2:2:-1 over said wavelength range and said first,  
second and third retarders (84, 86, 88) preferably are  
equivalent birefringent retarders or liquid crystal  
20 electrically rotatable retarders with their optic axes  
oriented relative to said reference axis at  $-\phi$ ,  $\phi+45^\circ$  and  $-\phi$ ,  
respectively, and said filter has its spectral transmission  
tunable by simultaneously rotating said birefringent retarders  
or liquid crystal retarders, mechanically or/and electrically,  
25 about said beam axis to change said angle  $\phi$  with the  
relationship of their orientation angles  $-\phi$ ,  $\phi+45^\circ$  and  $-\phi$   
remaining unchanged. ~~{Ex. FIG. 25}~~

47. (Currently amended) The spectral filter of claim 44  
30 is characterized in that said first, second, third and fourth  
polarization rotators (83, 85, 87, 89) preferably are  
dispersive Faraday rotators, to which magnetic fields are  
respectively applied, having their rotation angles in said

ratios of 1:-2:2:-1 over said wavelength range, and said first, second and third retarders (84, 86, 88) preferably are equivalent birefringent retarders with their optic axes oriented relative to said reference axis at  $-\phi$ ,  $\phi+45^\circ$  and  $-\phi$ , respectively, and said filter further comprises means for varying said Faraday rotation angles by adjusting the magnetic flux densities of said magnetic fields. ~~[Ex. FIG. 25]~~

48. (Currently amended) The spectral filter of claim 47 is characterized in that said filter has its spectral transmission tunable or switchable by simultaneously varying said Faraday rotation angles or switching said Faraday rotation angles in at least two alternative states with said ratios of 1:-2:2:-1 of said Faraday rotation angles remaining unchanged and functions as a one-direction device that transmits and tunably filters light in one direction, but blocks the backward light, with said birefringent retarders stationary and oriented relative to said reference axis such that their optic axes preferably are at  $-\phi=-22.5^\circ$ ,  $\phi+45^\circ=67.5^\circ$  and  $-\phi=-22.5^\circ$ , respectively, and said birefringent retarders at  $-\phi=-22.5^\circ$  having their retardation  $\Delta$  preferably equal or approximately equal to  $70.5^\circ$  over said wavelength range. ~~[Ex. FIG. 25]~~

49. (Currently amended) The spectral filter of claim 44 is characterized in that said first, second, third and fourth polarization rotators (83, 85, 87, 89) preferably are equivalent dispersive optical rotators and said first and third retarders (84, 88) preferably are variable retarders with their optic axes oriented parallel at  $-\phi$  relative to said reference axis, each having the retardation  $\Delta$  variable preferably in the range from  $60^\circ$  to  $100^\circ$  and said third retarder (86) preferably is a birefringent half-wave retarder

oriented at  $\phi+45^\circ$  relative to said reference axis, and said filter has the bandwidth of its spectral transmission peaks adjustable by simultaneously varying said retardation  $\Delta$  of variable retarders and its spectral transmission tunable by simultaneously rotating said variable retarders and said half-wave retarder in the same speed with said variable retarders synchronously in one direction and said half-wave retarder in the opposite direction to change said angle  $\phi$ . ~~[Ex. FIG. 25]~~

10           50. (Currently amended) The spectral filter of claim 44 is characterized in that said first, second, third and fourth polarization rotators (83, 85, 87, 89) preferably are equivalent dispersive optical rotators and said first, second and third retarders (84, 86, 88) preferably are variable  
15           retarders oriented relative to said reference axis with their optic axes at  $-\phi$ ,  $\phi+45^\circ$  and  $-\phi$ , respectively, which are operated to have their the retardation switchable in at least two alternative states such that in one of said switched states said variable retarders have their retardation equal or  
20           approximately equal to  $0^\circ$  and in the other state(s) said variable retarders at  $-\phi$  have their retardation valued preferably in the range from  $60^\circ$  to  $100^\circ$ , and said variable retarder at  $\phi+45^\circ$  has its retardation equal or approximately equal to  $180^\circ$  over said wavelength range.

25           51. (Currently amended) The spectral filter of claim 50 is characterized in that said filter has its spectral transmission switchable by simultaneously switching said variable retarders with their said retardation switched in  
30           said switched states, the bandwidth of its spectral transmission peaks adjustable by simultaneously varying said retardation of said variable retarders at  $-\phi$  with said variable retarder at  $\phi+45^\circ$  operated to have the retardation

equal or approximately equal to  $180^\circ$  over said wavelength range, and its spectral transmission tunable by simultaneously rotating said variable retarders about said beam axis in the same speed with said variable retarders at  $-\phi$  synchronously in  
 5 one direction and said variable retarder at  $\phi+45^\circ$  in the opposite direction to change the angle  $\phi$ . ~~[Ex. FIG. 25]~~

52. (Currently amended) The spectral filter of claim 6 is characterized in that said filter is a three-tuner spectral  
 10 filter without intermediate polarizer ~~according to claim 5~~ over said wavelength range comprising elements arranged in cascade along said light beam axis including an entrance polarizer (94);  
 a first polarization rotator (95), having its rotation angle  
 15  $\rho_{b1}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
 a first retarder (96);  
 a second polarization rotator (97), having its rotation angle  
 $\rho_{b2}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
 a second retarder (98);  
 20 a third polarization rotator (99), having its rotation angle  
 $\rho_{b3}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
 a third retarder (100);  
 a fourth polarization rotator (101), having its rotation angle  
 $\rho_{b4}(\lambda)$  varying as a function of light wavelength  $\lambda$ ;  
 25 an exit polarizer (102); and  
 means for rotating said retarders (96, 98, 100) about said beam axis;  
 said rotation angles  $\rho_{b1}(\lambda)$ ,  $\rho_{b2}(\lambda)$ ,  $\rho_{b3}(\lambda)$  and  $\rho_{b4}(\lambda)$  are in the ratios of  $\rho_{b1}(\lambda):\rho_{b2}(\lambda):\rho_{b3}(\lambda):\rho_{b4}(\lambda) = 3:-4:4:-3$  over said  
 30 wavelength range, said first, second and third retarders (96, 98, 100) have their retardation  $\Delta_1$ ,  $\Delta_2$  and  $\Delta_3$  valued such that the conditions  $30^\circ \leq \Delta_1 = \Delta_3 \leq 50^\circ$  and  $170^\circ \leq 2\Delta_1 + \Delta_2 \leq 220^\circ$  are

preferably satisfied over said wavelength range, and said first polarization rotator (95), first retarder (96), second polarization rotator (97), second retarder (98), third polarization rotator (99), third retarder (100) and fourth polarization rotator (101) are arranged in the recited order between said entrance and exit polarizers (94, 102) and oriented such that said entrance and exit polarizers (94, 102) are perpendicular to each other and the orientation angles of said first, second and third retarders (96, 98, 100) relative to said entrance polarizer (94) are  $3\phi$ ,  $-\phi$ , and  $3\phi$ , respectively, and in the ratios of  $3\phi:-\phi:3\phi=3:-1:3$ . ~~[Ex. FIG. 29]~~

53. (Currently amended) The spectral filter of claim 52 is characterized in that the combination of said polarization rotators (95, 97, 99, 101) and retarders (96, 98, 100) is equivalent to a series connection of three retarder-tuners (103, 104, 105) ~~in accordance with claim 5~~ with the first and third ones (103, 105) having identical retardation equal to  $\Delta_1$  and parallel oriented at angle of  $3(\rho_{b1}(\lambda)+\phi)$  and the central one (104) having the retardation equal to  $\Delta_2$  and orientation angle  $-(\rho_{b1}(\lambda)+\phi)$  and said filter has its spectral transmission determined by said rotation angles and defined by Equation (36a) or (36b) and tunable by simultaneously rotating said first, second and third retarders (96, 98, 100) about said beam axis with said first and third retarders (96, 100) synchronously in one direction and said second retarder (98) in the opposite direction to change their said orientation angles with said ratios of 3:-1:3 remaining unchanged or such that said first, second and third retarders (96, 98, 100) are parallel to said entrance polarizer, and further tunable by simultaneously varying said rotation angles  $\rho_{b1}(\lambda)$ ,  $\rho_{b2}(\lambda)$ ,  $\rho_{b3}(\lambda)$  and  $\rho_{b4}(\lambda)$  with said their ratios of

3:-4:4:-3 remaining unchanged over said wavelength range, its spectral transmission of square-waveform or approximate square-waveform with said retardation  $\Delta_1$ ,  $\Delta_2$  and  $\Delta_3$  preferably valued such that  $30^\circ \leq \Delta_1 = \Delta_3 \leq 50^\circ$  and  $170^\circ \leq 2\Delta_1 + \Delta_2 \leq 220^\circ$ ,

5 the slope of its maximum transmission peaks and the secondary maximum adjustable by simultaneously varying said retardation  $\Delta_1$ ,  $\Delta_2$  and  $\Delta_3$ , with the conditions  $30^\circ \leq \Delta_1 = \Delta_3 \leq 50^\circ$  and  $170^\circ \leq 2\Delta_1 + \Delta_2 \leq 220^\circ$  preferably maintained, and its spectral  
10 transmission inverted to work as a notch filter that tunably transmits and blocks light at wavelengths where said initial filter blocks and transmits light, respectively, when said exit polarizer (102) is rotated by  $90^\circ$  from said initial orientation to be parallel to said entrance polarizer (94).  
{Ex. FIG. 29}

15

54. (Currently amended) The spectral filter of claim 52 is characterized in that said first, second, third and fourth polarization rotators (95, 97, 99, 101) preferably are dispersive optical rotators with their rotation angles in said  
20 ratios of 3:-4:4:-3 over said wavelength range and said first, second and third retarders (96, 98, 100) preferably are equivalent birefringent retarders or liquid crystal electrically rotatable retarders, oriented such that their orientation angles relative to said entrance polarizer are in  
25 said ratios of 3:-1:3, and said filter is tunable by simultaneously rotating said birefringent retarders or liquid crystal retarders, mechanically or/and electrically, about said beam axis, with said ratios of 3:-1:3 of their said orientation angles remaining unchanged or such that said  
30 birefringent retarders or liquid crystal retarders are parallel to said entrance polarizer (94). {Ex. FIG. 29}

55. (Currently amended) The spectral filter of claim 52

is characterized in that said first, second, third and fourth polarization rotators (95, 97, 99, 101) preferably are dispersive Faraday rotators, to which magnetic fields are respectively applied, having their rotation angles in said  
5 ratios of 3:-4:4:-3 over said wavelength range and said first, second and third retarders (96, 98, 100) preferably are equivalent birefringent retarders with their optic axes oriented such that their orientation angles relative to said entrance polarizer (94) are in said ratios of 3:-1:3, and said  
10 filter further comprises means for varying said Faraday rotation angles by adjusting the magnetic flux densities of said magnetic field. ~~{Ex. FIG. 29}~~

56. (Currently amended) The spectral filter of claim 55  
15 is characterized in that said filter has its spectral transmission tunable or switchable by simultaneously varying said Faraday rotation angles or switching said Faraday rotation angles in at least two alternative states with said ratios of 3:-4:4:-3 of said Faraday rotation angles remaining  
20 unchanged over said wavelength range, and functions as a one-direction device that transmits and tunably filters light in one direction, but blocks the backward light, with said birefringent retarders stationary and oriented relative to said entrance polarizer (94) such that their optic axes  
25 preferably are at  $3\phi=67.5^\circ$ ,  $-\phi=-22.5^\circ$  and  $3\phi=67.5^\circ$ , respectively, and said retardation  $\Delta_1$  and  $\Delta_3$  preferably equal or approximately equal to  $38.4^\circ$  and said retardation  $\Delta_2$  equal or approximately equal to  $108.2^\circ$  over said wavelength range.  
~~{Ex. FIG. 29}~~

30

57. (Currently amended) The spectral filter of claim 52 is characterized in that said first, second, third and fourth polarization rotators (95, 97, 99, 101) preferably are



equivalent dispersive optical rotators and said first, second and third retarders (96, 98, 100) preferably are variable retarders, which are oriented relative to said entrance polarizer with the orientation angles of their optic axes in said ratios of 3:-1:3 and operated to have their the retardation switchable in at least two alternative states such that in one of said switched states said variable retarders have their retardation equal or approximately equal to  $0^\circ$  and in the other state(s) the variable retarders have their retardation valued to satisfy said conditions for the retardation over said wavelength range. ~~{Ex. FIG. 29}~~

58. (Currently amended) The spectral filter of claim 57 is characterized in that said filter has its spectral transmission switchable by simultaneously switching said variable retarders with their said retardation switched in said switched states, the slope of its maximum transmission peaks and the secondary maximum adjustable by simultaneously varying said retardation of said variable retarders with said conditions remaining satisfied, and its spectral transmission tunable by simultaneously rotating said variable retarders about said beam axis with said ratios of 3:-1:3 of their orientation angles remaining unchanged. ~~{Ex. FIG. 29}~~

59. (Currently amended) A method for wavelength-tunably filtering light over a wavelength range, comprising the steps of:  
providing a spectral filter ~~according to claim 6, the spectral filter~~ comprising an entrance polarizer, at least a dispersive polarization rotator and at least an orientation-sensitive polarizing element; and

tuning said spectral filter by rotating said polarizing element(s) or/and by varying the rotation angle(s) of said polarization rotator(s). ~~{Ex. FIGS. 7-11, 14, 16-18, 22, 24,~~

~~25, 29}~~

60. (Currently amended) The method of claim 59 is characterized in that said filter is a single-stage spectral  
5 filter ~~according to claim 8~~, comprising an entrance polarizer, a rotatable exit polarizer, and a dispersive polarization rotator, and said method comprises the step of tuning said single-stage filter by rotating said exit polarizer relative to said entrance polarizer or/and by varying the rotation  
10 angle of said dispersive polarization rotator. ~~{Ex. FIGS. 7, 8-10}~~

61. (Currently amended) The method of claim 60 is characterized in that said single-stage filter is modified  
15 ~~according to claim 12 or claim 14~~ to further comprise a rotatable half-wave retarder or an active polarization rotator, and said method further comprises the step of tuning said filter by rotating said retarder or varying the rotation angle of said active polarization rotator. ~~{Ex. FIGS. 8, 9}~~

20 62. (Currently amended) The method of claim 60 is characterized in that said single-stage filter is modified ~~according to claim 17~~ to further comprise a second dispersive polarization rotator and a variable retarder having its  
25 retardation switchable between two alternative states; and said method further comprises the step of tuning said filter by switching said retarder in said switched states. ~~{Ex. FIG. 10}~~

30 63. (Currently amended) The method of claim 59 is characterized in that said filter is an n-stage ( $n=2, 3, 4, \dots$ ) spectral filter ~~according to claim 19~~, the n-stage spectral filter comprising an entrance polarizer, n rotatable  
35 polarizers, and n dispersive polarization rotators with said entrance polarizer, n rotatable polarizers and n polarization

rotators arranged and said n rotatable polarizers is oriented  
~~in accordance with claim 19~~, said method comprising the step  
of tuning said n-stage filter by simultaneously rotating said  
n rotatable polarizers with the ratios of their azimuths  
5 remaining unchanged or so that said n rotatable polarizers are  
parallel or perpendicular to said entrance polarizer and  
further by simultaneously varying said rotation angles of said  
n polarization rotators with the ratios of their rotation  
angles remaining unchanged. ~~{Ex. FIGS. 11, 14, 16, 17}~~

10

64. (Currently amended) The method of claim 63 is  
characterized in that said n-stage filter is modified  
~~according to claim 23 or claim 25~~ to further comprise n  
rotatable half-wave retarders or n active polarization  
15 rotators, and said method further comprises the step tuning  
said n-stage filter by simultaneously rotating said n half-  
wave retarders with the ratios of their orientation angles  
remaining unchanged or such that said orientation angles are  
equal to zero or by simultaneously varying the rotation angles  
20 of said n active polarization rotators with their ratios  
remaining unchanged or equal or approximately equal to zero  
over said wavelength range. ~~{Ex. FIGS. 14, 16}~~

65. (Currently amended) The method of claim 63 is  
25 characterized in that said n-stage filter is modified  
~~according to claim 22~~ to further comprise another n dispersive  
polarization rotators and n identical variable retarders, each  
having its retardation switchable between two alternative  
states, and said method further comprises the step of tuning  
30 said filter by simultaneously switching said n variable  
retarders in said switched states or/and by simultaneously  
rotating said n retarders with the ratios of their said  
orientation angles remaining unchanged or such that each of  
said n retarders is parallel to its immediately preceding  
35 polarizer. ~~{Ex. FIG. 17}~~

66. (Currently amended) The method of claim 59 ~~is~~  
~~characterized in that said filter is a spectral filter without~~  
~~intermediate polarizer according to claim 30, claim 37, claim~~  
5 ~~44, or claim 52, the spectral filter without intermediate~~  
~~polarizer comprising an entrance polarizer, an exit polarizer,~~  
~~at least three dispersive polarization rotators and at least~~  
~~two retarders with said retarders oriented in accordance with~~  
~~claim 30, claim 37, claim 44, or claim 52, and wherein said~~  
10 ~~method comprises of the step of tuning said filter by~~  
~~simultaneously rotating said retarders {Ex. FIGS. 18, 24, 25,~~  
~~29} or said retarders and exit polarizer {Ex. FIG. 22} with the~~  
~~ratios of their orientation angles remaining unchanged or/and~~  
~~by simultaneously varying the rotation angles of said~~  
15 ~~polarization rotators with the ratios of said rotation angles~~  
~~remaining unchanged over said wavelength range or/and~~  
~~adjusting the transmission profile of said filter by varying~~  
~~the retardation of said retarders preferably in a~~  
~~predetermined range {Ex. FIGS. 18, 25, 29}. {Ex. FIGS. 18, 22,~~  
20 ~~24, 25, 29}~~

25.